



MANUFACTURED TO THE HIGHEST STANDARDS



H-1 REGISTERED



Certified Kosher Pareve



HALAL



ISO 21469 Certified



LUBRIPLATE® NSF H-1 REGISTERED FOOD MACHINERY GRADE LUBRICANTS

Lubriplate's complete line of high-performance, NSF H-1 Registered Food Machinery Grade Lubricants is manufactured under strict NSF/ISO 21469 Certified and ISO 9001 Registered quality control standards. Formulated with ingredients that comply with FDA regulation 21 CFR 178.3570 they can be used on machinery with incidental food contact. They are certified OU Kosher Pareve and HALAL registered. They meet USDA H-1 safety standards and are authorized for use in federally inspected meat and poultry plants.

Clean, safe and non-toxic, their use can significantly simplify your HACCP program by completely eliminating lubricants as a potential chemical hazard.

High Performance Synthetic and Pure USP White Mineral Oil-Based Lubricants.

NSF H-1 Registered Food Machinery Grade for Safe, Non-Toxic Lubrication.

FDA COMPLIANCE - With Regulations 21 CFR 178.3570, 21 CFR 178-3620, 21 CFR 172-878, 21 CFR 172.882 and 21 CFR 182.



Lubriplate®
Lubricants

Newark, NJ 07105 / Toledo, OH 43605 / 800-733-4755
www.lubriplate.com / LubeXpert@lubriplate.com



Backed By: **Lubriplate® ESP**

Extra Services Package

Plant Surveys / Tech Support / Training
Color Coded Lube Charts & Machine Tags
Lubrication Software / Follow-Up Oil Analysis

Lubriplate® NSF H-1 Registered, Food Grade Lubricants

Lubriplate's complete line of high-performance, NSF H-1 Registered, Food Machinery Grade Lubricants is designed to provide total food processing and bottling plant lubrication capability. Manufactured under strict NSF/ISO 21469 Certified and ISO 9001 Registered quality assurance standards, these lubricants are formulated from the highest quality base stocks combined with state-of-the-art anti-wear additives. They deliver a number of significant, cost effective advantages as outlined on the chart below.

All Lubriplate H-1 Lubricants are manufactured with ingredients that comply with FDA regulation 21 CFR 178.3570 for lubricants with incidental food contact. They meet USDA H-1 safety standards and are authorized for use in federally inspected meat and poultry plants. Clean, safe and non-toxic, their use can eliminate lubrication as a critical control point in HACCP programs.



Select Lubriplate H-1 Lubricants are formulated with LUBRI-ARMOUR® Anti-Microbial Additive. Developed to prevent the decomposition of lubricants caused by microorganisms, greases treated with LUBRI-ARMOUR® remain fresh and last longer in harsh food processing plant environments.



FEATURES	BENEFITS
Advanced High-Performance Formulations	Improved machinery life; decreased wear; reduced power consumption; extended lube intervals.
NSF H-1 Registered Products	Assures compliance with USDA / FDA guidelines and HACCP programs.
Multifunctional use	Reduces, consolidates and simplifies lubricant inventories and reduces lubricant misapplication.
Toll Free Technical Support 800-347-5343	Quick response to your lubrication questions.
Complimentary Plant Surveys	Identify opportunities for lubricant inventory consolidation and improvements.
No-charge Oil/Fluid and Grease Analysis	Helps determine lubricant and/or machinery condition and corrective measures needed.

F.D.A. CODES (CFR) FOR LUBRICANTS WITH INCIDENTAL FOOD CONTACT	
21.CFR 178-3570	Ingredients used to manufacture H-1 lubricants must comply with this code. / All Lubriplate H-1 products comply with this code.
21.CFR 178-3620	Technical White Mineral Oil as a component of non-food articles intended for use in contact with food. / The FMO Series complies.
21.CFR 172-878	USP White Mineral Oil for direct contact with food. / Lubriplate FMO Series complies with this code.
All of the mineral oil based products in the LUBRIPLATE H-1 range are formulated with USP White Mineral Oil which is both the purest and highest quality base oil any manufacturer can use to formulate H-1 lubricants.	
21.CFR 172-882	Synthetic isoparaffinic hydrocarbons, i.e., PAO base stocks / Lubriplate SFGO Ultra Series, SFL Series and the SYNXTREME FG Series.
21.CFR 182 with 9 subheadings	Substances Generally Recognized As Safe, e.g., zinc oxide and tocopherols (Vitamin E.)

NSF H-1 Registered, Food Processing Plant Application Recommendations

APPLICATIONS	LUBRIPLATE H-1 PRODUCT*	APPLICATIONS	LUBRIPLATE H-1 PRODUCT*
• GENERAL GREASING - NORMAL TEMPS HIGH TEMPERATURES LOW TEMPERATURES	SYNXTREME FG-2* or FGL-2* SYNXTREME FG-2* or FGL-2* SYNXTREME FG-1* or SFL-1*	• DRAFT & VENTILATING FANS GREASE OIL	SYNXTREME FG-2* or FGL-2* SFGO ULTRA-68* or FMO-350AW*
• GENERAL OILING	SFGO ULTRA-68* or FMO-350AW*	• STIRRUPS - BOTTLE FILLERS	STO-FG*
• CENTRALIZED GREASING SYSTEMS	FGL-0* or FGL-00*	• PEACH PITTERS - CHAIN DRIVES	FP-150L* or FP-150*
• SLIDES, CAMS, EXPOSED GEARS	PURE TAC*	• SEAMING ROLLS, SPINDLES, CHUCKS	SYNXTREME FG-1* or FGL-1*
• CHAINS, CONVEYORS, WIRE ROPE MEDIUM TEMPERATURES HIGH TEMPERATURES	SFGO ULTRA-7* or FP-150L* PGO-FGL-220*	• COOKERS - CARRIER BEARINGS	SYNXTREME FG-2* or PURE TAC*
• ENCLOSED GEAR CASES HELICAL GEARS WORM GEARS	SFGO ULTRA-220* or PGO-FGL-220* or FMO-1100AW* SFGO ULTRA-460* or PGO-FGL-460* or FMO-2400AW*	• COOKER VALVE LUBRICATION (MANZEL LUBRICATORS)	FOOD GRADE COOKER OIL*
• HOT BRAKE BEARINGS	SYNXTREME FG-2* or PURE TAC*	• ANGELUS SEAMERS (MANZEL LUBRICATORS)	SSO-FG 100* or SSO-FG-150* SEAMER OIL FG-100* or SEAMER OIL FG-150*
• AIR COMPRESSORS RECIPROCATING AIR COMPRESSORS ROTARY SCREW REFRIGERATION COMPRESSORS	SFGO ULTRA-68* or SFGO ULTRA 100* SFGO ULTRA-32* or SFGO ULTRA 46* RCO-68*	• SIGHT FEED OILERS	PM-500* or FP-150L*
• AIR LINE SYSTEMS	FMO-85AW* or FMO-150AW*	• ELECTRIC MOTOR BEARINGS	SYNXTREME FG-1* or FGL-1*
• HYDRAULIC SYSTEMS - NORMAL TEMPS LOW TEMPERATURES	SFGO ULTRA-68* or FMO-350AW* SFGO ULTRA-7* or FMO-85AW*	• STEAM VALVES & PEELERS	Consult LUBRIPLATE Tech Service 1-800-347-5343
• HIGH SPEED BEARINGS GREASE OIL	SFL-1* or FGL-1* SFGO ULTRA-32* or FMO-150AW*	• SCRUBBERS GREASE FITTINGS CHAIN DRIVES	SYNXTREME FG-2* or FGL-2* FP-150L* or FP-150*
• CHEMICAL & CONDENSATE PUMPS GREASE OIL	SYNXTREME FG-2* or FGL-2* SFGO ULTRA-68* or FMO-350AW*	• FORKLIFTS WHEEL BEARINGS HYDRAULIC OIL CHAIN LIFTS	SYNXTREME FG-2* or PURE TAC* SFGO ULTRA-68* or FMO-350AW* FP-150L*
• VACUUM PUMPS	SFGO ULTRA-68* or SFGO ULTRA 100*	• RUST PREVENTATIVE, LAYING UP	SFGO ULTRA-7* or FMO-350AW*
		• CLEANSING & FLUSHING FLUID / OIL	SYNFLUSH FG* or PURE FLUSH*
		• PAN DIVIDER OIL	PAN DIVIDER OIL*
		• LUBRIPLATE WHITE OILS	FMO SERIES*

Synthetic Based Product

Mineral Oil Based Product

*NSF H-1 Registered (Food Machinery Grade)

Lubriplate® Lubricants Company

Newark, NJ 07105 / Toledo, OH 43605 / 1-800-733-4755 / www.lubriplate.com / LubeXpert@lubriplate.com