



# Super-Duty Lubricants

## For all of Your Heavy Equipment

### Lubriplate® SYN-3002 Heavy-Duty, Moly-Fortified, Synthetic Grease.

- High performance, 100% synthetic, multi-purpose grease.
- Contains 5% Moly for extreme pressure applications.
- Recommended for all brands and types of heavy-duty equipment.

### Lubriplate® Gear Shield Extra Heavy

- Extreme pressure lubricant for all types of exposed gears.
- Excellent for use on fifth wheels, slides, pins and jacks.
- Available in caulk type cartridges and aerosol spray cans.

### Lubriplate® Chain & Cable Fluid Spray

- Cleans and lubricates all types of chains and cables.
- Excellent, non-gumming, multi-purpose penetrating oil.
- Prevents rust and corrosion. Loosens rusty nuts and bolts.

### Fiske's Kling Gear Oils

- SAE 80W-90 and 85W-140. Meets API specification GL-5.
- For heavy-duty gear applications, rear end differentials and recirculating systems.
- Red color, tacky, provides outstanding water separation.

### Fiske's AW Series Hydraulic Oils

- Excellent heavy-duty, general purpose hydraulic oils.
- AW/R+O fortified for maximum protection.
- ISO-32, 46 and 68 viscosity grades available.
- Available in a wide range of convenient packages.



**Lubricants You Can Trust From The Team You Can Trust!**



**Lubriplate Lubricants Company**

Newark, NJ 07105 / Toledo, OH 43605 / 1-800-733-4755  
www.lubriplate.com / LubeXpert@lubriplate.com

# Super-Duty Lubricants for all of your Heavy Equipment.

## Lubriplate® SYN-3001 & SYN-3002: Moly-Fortified, Polyalphaolefin (PAO)-Based, Synthetic Greases.

These high performance, heavy-duty, moly-fortified, synthetic greases provide superior oxidation resistance for long lasting protection from friction, wear and corrosion. They have excellent high and low temperature performance and are highly resistant to water. Contains 5% Moly. Recommended for all types of heavy equipment.

LUBRIPLATE PRODUCT	*PRODUCT PART NO.	NLGI GRADE	OIL VIS. cSt / SUS @ 40° C / 100° F	WORKED PENETRATION	ASTM DROP POINT	APPROX. COLD TEST	AW/EP	RUST/OXID. ADDITIVES	WATER RESISTANT
SYN-3001	L0315-	1	218 / 1009	310 / 340	500°F / 260°C	-50°F / -56°C	AW/EP	YES	YES
SYN-3002	L0316-	2	446 / 2066	265 / 295	500°F / 260°C	-45°F / -43°C	AW/EP	YES	YES

\*SYN-3000 Series Greases are available in Cartridges, Pails, 1/4 Drums & Drums. See below for package part number suffix.

## Lubriplate® Gear Shield Extra Heavy: Extreme Pressure Lubricant.

This heavy-duty, extreme pressure lubricant is formulated especially for the lubrication of exposed gears operating in adverse conditions. It is also excellent for use on fifth wheels, slides, pins and jack screws.

LUBRIPLATE PRODUCT	*PRODUCT PART NO.	NLGI GRADE	OIL VIS. cSt / SUS @ 40° C / 100° F	WORKED PENETRATION	ASTM DROP POINT	APPROX. COLD TEST	AW/EP	RUST/OXID. ADDITIVES	WATER RESISTANT
G.S. X-Heavy	L0152-	2.5	432 / 2000	235 / 260	370°F / 188°C	20°F / -7°C	AW/EP	YES	YES

\*Gear Shield Extra Heavy is available in Aerosol Cans, Caulk Type Cartridges, Pails, 1/4 Drums & Drums. See below for package part number suffix.

## Lubriplate® Chain & Cable Fluid Spray: Chain and Cable Lubricant and Penetrating Fluid.

An excellent non-gumming, penetrating oil. Cleans, penetrates and lubricates all types of wire rope, chains, and cables. Ideal for any moving metal surfaces. Prevents rust and corrosion. Protects brightwork, loosens rusty nuts and bolts. Excellent drilling, tapping, and sawing oil. Packed in handy 12 OZ. / 340 g. spray can. Part No. L0135-063.

## Fiske's Kling Gear Oils: Heavy-Duty, Extreme Pressure (EP) Gear Oils.

These Heavy-duty, tacky, oils cling tenaciously to gear teeth. Formulated for heavy service and fortified with extreme pressure additives, these oils help minimize wear and prolong gear life. For heavy-duty gear applications, rear end differentials and recirculating systems. They provide excellent rust and oxidation protection. They meet MIL-L-2105C specifications and conform to API classification GL-5.

FISKE'S KLING GEAR	*PRODUCT PART NO.	ISO VIS. GRADE	AGMA NO.	SAE GEAR OIL NO.	VIS. SUS @100°F / 210°F	VIS. INDEX	FLASH POINT	FIRE POINT	POUR POINT
KG 80W-90	F0162-	150	5 EP	80W-90	816 / 89	114	410°F / 210°C	460°F / 238°C	-25°F / -32°C
KG 85W-140	F0163-	460	7 EP	80W-140	1866 / 140	107	390°F / 199°C	435°F / 224°C	-10°F / -23°C

\*Fiske's Kling Gear Oils are available in Pails, 1/4 Drums & Drums. See below for package part number suffix.

## Fiske's AW Series: Heavy-Duty Hydraulic Oils.

These High performance, anti-wear fortified oils are formulated for all types of hydraulic and recirculating systems found on industrial and construction equipment. They are fortified with rust and oxidation inhibitors. The anti-wear additive package helps minimize the formation of sludge and other corrosive by-products. High aniline points help prolong seal life. Meets Cincinnati Milacron and Vickers specifications.

FISKE'S AW SERIES	*PRODUCT PART NO.	ISO VIS. GRADE	SAE NUMBER	VIS. cSt @40°C	VIS. SUS @100°F / 210°F	VIS. INDEX	FLASH POINT	FIRE POINT	POUR POINT
AW-32	F0400-	32	10	29	154 / 44	97	405°F / 207°C	445°F / 230°C	-25°F / -32°C
AW-46	F0401-	46	20	42	213 / 48	99	410°F / 210°C	450°F / 232°C	-20°F / -29°C
AW-68	F0402-	68	20	61	314 / 54	103	430°F / 221°C	470°F / 243°C	-10°F / -23°C

\*Fiske's AW Series Oils are available in Pails & Drums. See below for package part number suffix.

## Packaging / Part Number Information:

Add the Package Part Number Suffix listed on the chart below to the Product Part Number.

ITEM / PACKAGE	12 CT. / 11 OZ. SPRAY CANS	40 CT. / 15.5 OZ CARTRIDGES	40 CT. / 10.5 OZ CAULK CARTRIDGE	35 LB. / 5 GAL PAIL	120 LB. / 16 GAL QTR. DRUM	400 LB. / 55 GAL DRUM
GREASES*	-063	-098	-000	-035	-039	-040
KLING GEAR OILS*	-	-	-	-035	-039	-040
AW HYD OILS	-	-	-	-060	-	-062

\*Items Sold By Weight.

## Lubriplate Lubricants Company

Newark, NJ 07105 / Toledo, OH 43605 / Phone: 1-800-733-4755 / Website: [www.lubriplate.com](http://www.lubriplate.com) / E-mail: [lubeXpert@lubriplate.com](mailto:lubeXpert@lubriplate.com)