



# Lubri-Topics

## Lubriplate® LTR-2 Provides Effective Lubrication Solutions For Construction, Quarry, Mining And Aggregate Industries.

### Lubriplate® LTR-2

Heavy-Duty, Tacky, Red, Lithium Complex Grease.

This rugged, tacky, highly water resistant, extreme pressure grease can withstand higher temperatures than traditional lithium greases. The film strength and shear stability of this product is exceptional, resulting in wear reduction and long lubricant life. It is recommended for a wide variety of heavy-duty construction, quarry, aggregate and mining applications. Red in color.



#### Specifications

NLGI GRADE	BASE OIL VIS. cSt @ 40°C	WORKED PENETRATION	ASTM DROP POINT	AW/EP
2	460	265 / 295	505°F / 263°C	AW/EP

#### Available Packaging / Part Number

CARTRIDGES 14.5 OZ / 411 g	PAILS 35 LB / 15.9 kg	QUARTER DRUMS 120 LB / 54 kg	FULL DRUMS 420 LB / 191 kg
L0167-098	L0167-035	L0167-039	L0167-040

#### Lubriplate LTR-2 Interchange Recommendations

Chevron Ultra Duty No. 2	Lubriplate LTR-2
Citgo Mystic JT-6	Lubriplate LTR-2
Lubrication Engineers Almatek 1232	Lubriplate LTR-2
Lubrication Engineers Almaplex 1275	Lubriplate LTR-2
Lubrication Engineers Almagard 3752	Lubriplate LTR-2
Lubrication Engineers Multiplex 4622	Lubriplate LTR-2
Shell Retinax No. 2	Lubriplate LTR-2
Texaco Starplex No. 2	Lubriplate LTR-2
Texas Refining Company TRC-Red	Lubriplate LTR-2

## Go GREEN! With Lubriplate® Biodegradable Penetrating Oil Multi-Purpose Lubricating Fluid:

The ECO-Friendly, Biodegradable, Vegetable-Based, Multi-Purpose Spray Lubricant.

An environmentally friendly, Readily Biodegradable (Pw1), bio-based, lubricating oil for general lubrication of hinges, locks, latches, slides, chains, cables or anywhere metal contacts metal. Ideal for trucks, cars, boats, bicycles, garden equipment, guns, tools, office equipment, garage doors, farm equipment and golf courses. Provides a long lasting protective film that prevents friction, wear, rust and corrosion. Excellent moisture displacement properties.

Available in 11 OZ. / 312 g. spray can, Part No. L0721-063.  
and in 14 OZ. / 414 ml. non-aerosol, hand pump, spray bottle. Part No. L0721-067.



## Lubriplate® Offers A Wide Range Of High-Quality Spray Lubricants To Meet Your Needs.



### **Chain & Cable Fluid - Penetrating Oil:**

A superior, cleansing, non-gumming penetrating oil for wire rope, chains, cables and general lubrication. Prevents rust and corrosion and protects brightwork. Loosens rusty nuts and bolts. Excellent drilling, tapping, and sawing oil.

Packed In 12 OZ. / 340 g. spray can. Part No. L0135-063.

### **Spray Lube “A” White Lithium Grease:**

A multi-purpose, white lithium-based lubricant of medium density. Sprays like a fluid, congeals to a grease. Excellent for latches, locks, hinges, battery terminals and other hardware.

Packed In 11 OZ. / 311.8 g. spray can. Part No. L0034-063.

### **Gear Shield Extra Heavy:**

Developed for easy lubrication of open gears. A tough, tacky grease. Excellent for fifth wheel applications. Packed in handy 11 OZ. / 311.8 g. spray can. Part No. L0152-063.

### **X-357 - Extreme Pressure Lubricant:**

An extreme pressure lubricant that penetrates and adheres. Water resistant and unaffected by temperature extremes. For use on pintle hooks, slide axles, open gears, fifth wheels. Contains moly-disulfide.

Packed in 11 OZ. / 311.8 g. spray can. Part No. L0149-063.

### **Marine & Auto Guard:**

Multi-purpose penetrating oil. An excellent “wet start” product. Spray on wet plug wires and distributor cap. Excellent moisture displacement properties. Prevents rust and corrosion. Excellent fogging oil.

Packed in 12 OZ. / 340 g. spray can. Part No. L0774-063.

### **Metalworking Fluid Aerosol:**

A specially developed product for metalworking operations. Excellent for drilling, tapping, sawing, and grinding. Packed in handy 12 OZ. / 340 g. spray can. Part No. L0185-063.

### **Oil Well In a Bottle™**

An excellent multi-purpose, penetrating oil ideal for slides, hinges, rollers, cables, frozen nuts and bolts. Prevents rust and corrosion. Moisture displacing agent works on wet ignition for “wet start.” Packed in 14 OZ. / 414 ml. non-aerosol, hand pump, spray bottle. Part No. L0188-067.

## Many Lubriplate® NSF H-1 Registered, Food Machinery Grade Lubricants Are Also Available In Sprays.

### **FGL-1 Spray:**

Class H-1 lubricant in handy, easy to use 11 OZ. / 312 g. spray can. Quick and clean applications. Fortified with anti-wear, anti-rust, and anti-corrosion additives. Part No. L0231-063.

### **FMO-350-AW Spray:**

A multi-purpose, Anti-wear fortified, food machinery oil, in easy to apply spray can. For use where a Class H-1 oil is required. Part No. L0882-063.

### **Super FML-2 Spray:**

A Class H-1 white lubricant in handy, easy to use spray can. For use in food processing operations where a Class H-1 lubricant is required. Part No. L0145-063.

### **SFGO Ultra-7 Spray:**

A multi-purpose, synthetic, chain and penetrating fluid spray lubricant, for use on bottling, dairy and food processing machinery. For chains, slides, tools and general lubrication. Part No. L0912-063.

### **Food Grade Silicone Lubricant:**

A multi-purpose, silicone lubricant for use on bottling, dairy and food processing machinery. For slides, chains, O-rings, rubber seals and general lubrication. Part No. L0723-063.

### **FMO-85-AW Spray:**

A multi-purpose Class H-1 oil. Packed in 14 OZ. / 414 ml non-aerosol pump spray bottle. Part No. L0880-067.

