



ISO-9001 Registered Quality System.

Sales, Service & Distribution Center

Newark, NJ 07105

Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605

Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE No.'s 130-A & 130-AA

DESCRIPTION

LUBRIPLATE No's. 130-A & 130-AA are designed for those applications where a grease-type lubricant possessing extremely good water repellency and superior lubrication characteristics are desired.

APPLICATIONS

These products are recommended for:

- ⇒ Plain bearings
- ⇒ Cams
- ⇒ Guides
- ⇒ Open gears
- ⇒ Slides and chassis lubrication
- ⇒ Where temperatures do not exceed 170°F



Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*	
		No. 130-A	No. 130-AA
Type of Base		Calcium	Calcium
Worked Penetration	ASTM D-217	235/260	310/340
NLGI No.		2.5	1
ASTM Melting Point	ASTM D-87	200°F/93°C	190°F/88°C
Mineral Oil Viscosity SUS @ 100F	ASTM D-2161	750	750
cSt @ 40C	ASTM D-445	135	135
Color	Visual	Beige	Beige
Character		Smooth	Smooth

PACKAGING AVAILABLE

No. 130-A

No. 130-AA

Carton, 12/16 oz. Plastic Tubs

L0043-004

L0044-004

Carton, 4/6 lb. Plastic Tubs

L0043-005

L0044-005

35 lb. Pail

L0043-035

L0044-035

120 lb. Quarter Size Drum

L0044-039

420 lb. Full Size Drum

L0043-040

L0044-040

Carton, 36/1¼ oz. Tubes (1X6)

L0044-086

Carton, 36/10 oz. Plastic Tubes

L0044-092