



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE MULTI-LUBE "A"

DESCRIPTION

LUBRIPLATE Multi-Lube "A" is an anhydrous calcium, NLGI No. 2 grade, non-corrosive, extreme pressure, water resistant, multi-purpose lubricant with a workable range of -20°F to 210°F.

APPLICATIONS

LUBRIPLATE Multi-Lube "A" is recommended for both plain and anti-friction bearings, cams, slides and open gears. This lubricant is especially suited for wet applications as it is very resistant to moisture and many other liquid contaminants.

Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Type of Base		Anhydrous Calcium
Worked Penetration	ASTM D-217	265 to 295
NLGI No.		2
Dropping Point	ASTM D566	280°F/138°C
Mineral Oil Viscosity SUS @ 100°F	ASTM D-2161	500
cSt @ 40°C	ASTM D-445	95
Oxidation Stability	ASTM D-942	Excellent
Color	Visual	Beige
Character	Visual	Smooth



PACKAGING AVAILABLE

35 lb. Pail
120 lb. Quarter Size Drum
430 lb. Full Size Drum

Part No.

L0183-035
L0183-039
L0183-040