



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE SUPER CHAIN OIL

DESCRIPTION

LUBRIPLATE Super Chain Oil is a high viscosity, tenacious type, high flash oil containing micro-fine graphite to provide smokeless lubrication of oven chains and other heavy-duty chain operations throughout a wide temperature operating range.

⇒ Contains micro-fine graphite

APPLICATIONS

LUBRIPLATE Super Chain Oil is recommended for bakery ovens, drying ovens and other type ovens where the temperature does not exceed 450°F. It is also recommended for all other types of heavy-duty chain operations such as floor chain conveyors, assembly lines, warehouse distribution lines, car washes and similar operations. LUBRIPLATE Super Chain Oil can be fed through automatic lubricators that can handle a SAE 140 grade lubricant. It can be brushed on, swabbed and drip fed.

ADVANTAGES

⇒ The high flash point of 550°F (288°C) and the fact that it does not smoke at elevated temperatures, makes it ideal as an oven chain lubricant.



Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Viscosity: SUS @ 100°F	ASTM D-2161	2600
cSt @ 40°C	ASTM D-445	497
SUS @ 210°F	ASTM D-2161	155
cSt @ 100°C	ASTM D-445	32
ISO Grade	ASTM D-2422	460
API Gravity	ASTM D-287	27.4
Flash Point	ASTM D-92	550°F/288°C
Fire Point	ASTM D-92	625°F/330°C
Pour Point	ASTM D-97	5°F/-15°C

PACKAGING AVAILABLE

Carton, 4/1 Gallon Jugs
5 Gallon Pail
16 Gallon Drum
55 Gallon Drum

Part No.

L0857-057
L0857-060
L0857-061
L0857-062