



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE SYN MPFG-7

"These products are certified OU Kosher Pareve"

*NSF International H-1 Registered
NSF ISO21469 Certification

DESCRIPTION

LUBRIPLATE SYN MPFG-7 is a 100% polyalphaolefin (PAO) synthetic fluid. It is an NSF International H-1 Registered* food grade product for applications in the food processing industry.

APPLICATIONS

LUBRIPLATE SYN MPFG-7 is recommended to lubricate plastic modular wear strips and sprockets; as a barrier fluid; and for applications where extreme low temperature fluid is required.

STORAGE RECOMMENDATIONS

Product should be stored in a dry covered area between 40°F to 120°F, away from direct sunlight.

Open containers, temperature, moisture may alter normal shelf-life.

Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Viscosity cSt @ 40°C	ASTM D-445	6.67
Viscosity SUS @ 100°F	ASTM D-2161	47.5
Viscosity SUS @ 210°F	ASTM D-2161	33
Gravity Specific @15.6 C	ASTM D-4052	0.803
Total Acid Number	ASTM D97	0.02
Flash Point	ASTM D-92	190°C
Pour Point	ASTM D-97	-54°C
Color, Saybolt	ASTM D-1500	0.5 Max

PACKAGING AVAILABLE

55 Gallon Drum

Part No.

L1008-062

*NSF International H-1 Registration No.

(Meets former USDA 1998 Guidelines)

151874

*Registered H-1 by NSF International for use in food processing facilities as a lubricant or anti-rust agent on equipment in which there may be incidental contact involving the lubricated part and the edible product.

"LUBRIPLATE SYN MPFG-7 contains no components derived from TSE/BSE relevant animal species; therefore, it is compliant with the requirements of the TSE Note for Guidance EMA/410/01 Rev. 3 July 2011."

