



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center
Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center
Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support
Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE SYNXTREME HT MAX

DESCRIPTION

LUBRIPLATE SYNXTREME HT MAX is PTFE thickened fluorinated grease that is used for high temperature applications and applications where chemical and solvent resistance is needed. This grease is fortified with a corrosion inhibitor.

APPLICATIONS

- ⇒ High Temperature Rolling Element Applications
- ⇒ Applications requiring Chemical and Solvent Resistance
- ⇒ Effective for oxygen service

ADVANTAGES

- ⇒ Synthetic Grease – NLGI Grade 2
- ⇒ Excellent Thermoxidative and Hydrolytic Stability
- ⇒ Operating Temperature Range -20°C(-4°F) to 288°C(550°F)
- ⇒ Low Volatility and Oil Separation
- ⇒ Fortified to Protect Ferrous Metals from Rusting
- ⇒ Extremely inert
- ⇒ NSF H1 Registered Food Grade

SAFETY

LUBRIPLATE SYNXTREME HT MAX is not hazardous. See the Safety Data Sheet for additional safety related information on the grease.



Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Typical Base Oil Properties		
Chemistry	Report	Perfluoropolyether
Kinematic Viscosity 40°C	ASTM D-445	488 cSt
Kinematic Viscosity 100°C	ASTM D-445	46 cSt
Viscosity Index	ASTM D-2270	150
Flash Point	ASTM D-92	None
Pour Point	ASTM D-97	-30°C
Typical Grease Properties		
Color	Visual	White
Appearance	Visual	Smooth
Penetration Unworked	ASTM D-217	288
Penetration 60 Strokes	ASTM D-217	285
NLGI Grade	ASTM D-217	2
Oil Separation, 24h at 100°C	ASTM D-6184	1.93%
Evaporation, 24h at 100°C	CTM-1	0.04%
Dropping Point	ASTM D-2265	>600°
Ferrous Corrosion Prevention, DI Water	CTM	>168h
Density, 25°C	CTM-2	1.98 g/cc
Copper Corrosion, 24h at 100°C	ASTM D-4048	1B
Oxidation Induction Time (PDSC)	MIL PRF 32014, 250°C	>120 min
Four Ball Extreme Pressure	ASTM D-2596	>8000N, >800Kg

PACKAGING AVAILABLE

Carton, 1 – 28 oz. Cartridge

Part No.

L0331-002

***NSF International H-1 Registration No.**
(Meets former USDA 1998 Guidelines)

153949

**Registered H-1 by NSF International for use in food processing facilities as a lubricant or anti-rust agent on equipment in which there may be incidental contact involving the lubricated part and the edible product.*

LUBRIPLATE SYNXTREME HT Max contains no components derived from TSE/BSE relevant animal species; therefore, it is compliant with the requirements of the TSE Note for Guidance EMA/410/01 Rev. 3 July 2011."