



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center
Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center
Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support
Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE No. 78 OIL-ZF*

DESCRIPTION

LUBRIPLATE No. 78 Oil-ZF* is designed for use in the Manzel Lubricator on A-B/FMC style rotary cookers/sterilizers.

APPLICATIONS

LUBRIPLATE No. 78 Oil-ZF* was developed specifically for applications, where there are various and different types of cleaning compounds used.

ADVANTAGES

LUBRIPLATE No. 78 Oil-ZF* is compounded with additives that impart a superior anti-wear and load-carrying film on the lubricated surfaces. This product also delivers corrosion resistance and reduces oxidation and sludge.

*Zinc Free

STORAGE RECOMMENDATIONS

1. Products should be stored between 40°F-120°F.
2. Products should be stored in a dry covered environment.
3. Products should not be stored in warm, direct sunlight.
4. improper storage conditions can significantly alter the shelf life of the product. Such conditions would include temperature, moisture, open containers, etc.



Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Viscosity SUS @ 210°F	ASTM D-2161	85
Viscosity cSt @ 100°C	ASTM D-445	16.9
Viscosity SUS @ 100°F	ASTM D-2161	820
Viscosity cSt @ 40°C	ASTM D-445	183
Viscosity Index	ASTM D-2270	98
ISO Grade		150
Approximate SAE No.		90
Flash Point	ASTM D-92	390°F/199°C
Fire Point	ASTM D-92	450°F/232°C
Pour Point	ASTM D-97	-20°F/-28.9°C
API Gravity	ASTM D-287	27.8

PACKAGING AVAILABLE

	<u>Part No.</u>
5 Gallon Pail	L0699-060
55 Gallon Drum	L0699-062
330 Gallon Bin	L0699-070
275 Gallon Bin	L0699-072