



ISO-9001 Registered Quality System.  
ISO-21469 Compliant.

#### Sales, Service & Distribution Center

Newark, NJ 07105  
Phone: 973-589-9150 Fax: 973-589-4432

#### Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605  
Phone: 419-691-2491 Fax: 419-693-3806

#### Sales and Tech Service Support

Phone: 1-800-733-4755

## PRODUCT DATA

# LUBRIPLATE FP-150 & FP-150-L

"These products are certified OU Kosher Pareve"

"These products are Halal certified"

\*NSF International H-1 Registered  
NSF ISO21469 Certification

## DESCRIPTION

LUBRIPLATE FP-150 and LUBRIPLATE FP-150-L are tacky, waterproof adhesive oils, which will resist heavy water wash down and steam. They are NSF International H-1 Registered oils for use in helical gear boxes, chains, linkages, cams, slides and wherever a drip-less adhesive fluid lubricant is desired.

## APPLICATIONS

- ⇒ Chains, Conveyors, Wire Rope
- ⇒ Peach Pitters – Chain Drivers
- ⇒ Sight Feed Oilers
- ⇒ Scrubbers, Grease Fittings, Chain Drives
- ⇒ Forklifts, Wheel Bearings, Hydraulic Oil Chain Lifts

## ADVANTAGES

- ⇒ Clean, safe, non-toxic lubrication

*\*Registered H-1 by NSF International for use in food processing facilities as a lubricant or anti-rust agent on equipment in which there may be incidental contact involving the lubricated part and the edible product.*

*"LUBRIPLATE FP-150 and LUBRIPLATE FP-150-L contain no components derived from TSE/BSE relevant animal species; therefore, it is compliant with the requirements of the TSE Note for Guidance EMA/410/01 Rev. 3 July 2011".*

## Typical Test Data

| PROPERTY                  | TEST METHOD | TYPICAL RESULTS* |                 |
|---------------------------|-------------|------------------|-----------------|
|                           |             | FP-150           | FP-150-L        |
| Viscosity:<br>SUS @ 100°F | ASTM D-2161 | 1950             | 510             |
| cSt @ 40°C                | ASTM D-445  | 367              | 103             |
| SUS @ 210°F               | ASTM D-2161 | 126              | 67              |
| cSt @ 100°C               | ASTM D-445  | 25               | 12              |
| Viscosity Index           | ASTM D-2270 | 93               | 108             |
| API Gravity               | ASTM D-287  | 28.4             | 30.2            |
| Flash Point               | ASTM D-92   | 395°F/<br>202°C  | 410°F/<br>210°C |
| Fire Point                | ASTM D-92   | 455°F/<br>235°C  | 450°F/<br>232°C |
| Pour Point                | ASTM D-97   | 0°F/<br>-18°C    | -5°F/<br>-21°C  |

## PACKAGING AVAILABLE

Carton, 4/1 Gallon Plastic Jugs  
5 Gallon Pail  
16 Gallon Drum  
55 Gallon Drum

## FP-150

L0735-057  
L0735-060  
L0735-061  
L0735-062

## FP-150-L

L0736-057  
L0736-060  
L0736-061  
L0736-062

**\*NSF International H-1 Registration No.'s**  
(Meets former USDA 1998 Guidelines)

**126123**

**126124**

