



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center
Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center
Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support
Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE FP-150 & FP-150-L

"These products are certified OU Kosher Pareve"
"These products are Halal certified"

*NSF International H-1 Registered
NSF ISO21469 Certification

DESCRIPTION

LUBRIPLATE FP-150 and LUBRIPLATE FP-150-L are tacky, waterproof adhesive oils, which will resist heavy water wash down and steam. They are NSF International H-1 Registered oils for use in helical gear boxes, chains, linkages, cams, slides and wherever a drip-less adhesive fluid lubricant is desired.

APPLICATIONS

- ⇒ Chains, Conveyors, Wire Rope
- ⇒ Peach Pitters – Chain Drivers
- ⇒ Sight Feed Oilers
- ⇒ Scrubbers, Grease Fittings, Chain Drives
- ⇒ Forklifts, Wheel Bearings, Hydraulic Oil Chain Lifts

ADVANTAGES

- ⇒ Clean, safe, non-toxic lubrication

**Registered H-1 by NSF International for use in food processing facilities as a lubricant or anti-rust agent on equipment in which there may be incidental contact involving the lubricated part and the edible product.*

"LUBRIPLATE FP-150 and LUBRIPLATE FP-150-L contain no components derived from TSE/BSE relevant animal species; therefore, it is compliant with the requirements of the TSE Note for Guidance EMA/410/01 Rev. 3 July 2011".

STORAGE RECOMMENDATIONS

1. Products should be stored between 40°F-120°F.
2. Products should be stored in a dry covered environment.
3. Products should not be stored in warm, direct sunlight.
4. improper storage conditions can significantly alter the shelf life of the product. Such conditions would include temperature, moisture, open containers, etc.

Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*	
		FP-150	FP-150-L
Viscosity:			
SUS @ 100°F	ASTM D-2161	1950	510
cSt @ 40°C	ASTM D-445	367	103
SUS @ 210°F	ASTM D-2161	126	67
cSt @ 100°C	ASTM D-445	25	12
Viscosity Index	ASTM D-2270	93	108
API Gravity	ASTM D-287	28.4	30.2
Flash Point	ASTM D-92	395°F/ 202°C	410°F/ 210°C
Fire Point	ASTM D-92	455°F/ 235°C	450°F/ 232°C
Pour Point	ASTM D-97	0°F/ -18°C	-5°F/ -21°C

PACKAGING AVAILABLE

	FP-150	FP-150-L
Carton, 4/1 Gallon Plastic Jugs	L0735-057	L0736-057
5 Gallon Pail	L0735-060	L0736-060
16 Gallon Drum	L0735-061	L0736-061
55 Gallon Drum	L0735-062	L0736-062

***NSF International H-1 Registration No.'s**
(Meets former USDA 1998 Guidelines)

126123

126124

