



ISO-9001 Registered Quality System.  
ISO-21469 Compliant.

**Sales, Service & Distribution Center**  
Newark, NJ 07105  
Phone: 973-589-9150 Fax: 973-589-4432

**Manufacturing, Sales, Service & Distribution Center**  
Toledo, OH 43605  
Phone: 419-691-2491 Fax: 419-693-3806

**Sales and Tech Service Support**  
Phone: 1-800-733-4755

## PRODUCT DATA

# LUBRIPLATE STO-FG

"This product is certified OU Kosher Pareve"  
"This product is Halal certified"

\*NSF International H-1 Registered  
NSF ISO21469 Certification

### DESCRIPTION

LUBRIPLATE STO-FG is a special, compounded oil recommended for the lubrication of stirrups on bottle filling machines.

### APPLICATIONS

⇒ Stirrups – Bottle Fillers

### ADVANTAGES

LUBRIPLATE STO-FG has excellent emulsifying properties to provide a lubricating film on the metal surfaces even in the presence of excessive moisture. LUBRIPLATE STO-FG is also compounded with dispersant type additives to keep the metal surfaces from building up with undesirable residues. This anti-wear oil is designed for areas of "incidental contact" requiring an NSF International H-1 registered product.

### Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Viscosity SUS @ 100°F	ASTM D-2161	350
Viscosity cSt @ 40°C	ASTM D-445	67
ISO		68
SAE Viscosity		20
API Gravity	ASTM D-287	29.0
Color	ASTM D-1500	0.0
Flash Point °F/°C	ASTM D-92	425°F/219°C
Fire Point °F/°C	ASTM D-92	485°F/252°C
Pour Point °F/°C	ASTM D-97	-15°F/-26°C
Four Ball Wear Test	ASTM D-2266	.36 mm

### PACKAGING AVAILABLE

### Part No.

5 Gallon Pail

L0863-060

55 Gallon Drum

L0863-062



\*NSF International H-1 Registration No.  
(Meets former USDA 1998 Guidelines)

126120

\*Registered H-1 by NSF International for use in food processing facilities as a lubricant or anti-rust agent on equipment in which there may be incidental contact involving the lubricated part and the edible product.

"LUBRIPLATE STO-FG contains no components derived from TSE/BSE relevant animal species; therefore, it is compliant with the requirements of the TSE Note for Guidance EMA/410/01 Rev. 3 July 2011."