



ISO-9001 Registered Quality System.  
ISO-21469 Compliant.

### Sales, Service & Distribution Center

Newark, NJ 07105  
Phone: 973-589-9150 Fax: 973-589-4432

### Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605  
Phone: 419-691-2491 Fax: 419-693-3806

### Sales and Tech Service Support

Phone: 1-800-733-4755

## PRODUCT DATA

# LUBRIPLATE PM-500

"This product is certified OU Kosher Pareve"  
"This product is Halal certified"

\*NSF International H-1 Registered  
NSF ISO21469 Certification

## DESCRIPTION

LUBRIPLATE PM-500 contains emulsifying agents, which wet the lubricated surfaces and provide an oiliness film for moving parts.

## APPLICATIONS

LUBRIPLATE PM-500 has been and is being used, very successfully, in pear machines and other applications where an NSF International H-1 registered\* white oil is required. LUBRIPLATE PM-500 is specially suited for water conditions existing in the machinery operation.

## ADVANTAGES

⇒ USP Grade White Oil used in these formulations.

*"LUBRIPLATE PM-500 contains no components derived from TSE/BSE relevant animal species; therefore, it is compliant with the requirements of the TSE Note for Guidance EMA/410/01 Rev. 3 July 2011".*

*\*Registered H-1 by NSF International for use in food processing facilities as a lubricant or anti-rust agent on equipment in which there may be incidental contact involving the lubricated part and the edible product.*

*Manufactured with ingredients that comply with FDA 21 CFR 178.3570.*

## Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Viscosity SUS @ 100°F	ASTM D-2161	530
Viscosity cSt @ 40°C	ASTM D-445	101
Viscosity SUS @ 210°F	ASTM D-2161	63
Viscosity cSt @ 100°C	ASTM D-445	10.8
API Gravity	ASTM D-287	28.7
Color	ASTM D-1500	0.0
Flash Point	ASTM D-92	420°F/216°C
Fire Point	ASTM D-92	485°F/252°C
Pour Point	ASTM D-97	-5°F/-21°C
SAE Viscosity		30
ISO Viscosity		100

## PACKAGING AVAILABLE

35 lb. Drum  
405 lb. Drum

## Part No.

L0192-035  
L0192-040

**\*NSF International H-1 Registration No.**  
(Meets former USDA 1998 Guidelines)

**126122**

