



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE PURE TAC LIGHT

"This product is certified OU Kosher Pareve"

"This product is Halal certified"

*NSF International H-1 Registered
NSF ISO21469 Certification

DESCRIPTION

LUBRIPLATE Pure Tac Light is an H-1/food grade grease which may be pumped through an automatic greasing system to lubricate bearings and open gears at food, beverage and pharmaceutical processing facilities. It is manufactured with pure USP mineral oil and other additives which are approved by the FDA 21 CFR 178.3570. It is very adhesive and resistant to water and caustic washdown solutions.

***Now formulated with LUBRI-ARMOUR, LUBRIPLATE's anti-microbial additive developed to prevent the decomposition of lubricants caused by microorganisms. LUBRIPLATE Pure Tac Light, treated with LUBRI-ARMOUR remains fresh and lasts longer in harsh food processing plant environments.**

APPLICATIONS

Registered greases are designed for applications subjected to chemically treated water, heat and steam. For all types of medium to slow speed bearings, open gears and hydrostatic cooker chains.

ADVANTAGES

- ⇒ USP Mineral Oil-Based Food Grade Grease
- ⇒ Highly water resistant

Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*
NLGI Consistency		1.5
Worked Penetration	ASTM D-217	290 - 320
Dropping Point °C/°F	ASTM D-566	253°C/488°F
Copper Corrosion	ASTM D-130	1b
Soap Type		Aluminum Complex
Color	ASTM D-1500	White
Texture		Tacky/Adhesive
Viscosity cSt @ 40°C	ASTM D-445	600
SUS @ 100°F	ASTM D-2161	3170

PACKAGING AVAILABLE

Part No.

35 lb Pail	L0235-035
120 lb. Quarter Size, Drum	L0235-039
415 lb. Full Size, Drum	L0235-040
Carton, 40/13.5 oz. Cartridges	L0235-098

***NSF International H-1 Registration No.**
(Meets former USDA 1998 Guidelines)

141506

**Registered H-1 by NSF International for use in food processing facilities as a lubricant or anti-rust agent on equipment in which there may be incidental contact involving the lubricated part and the edible product.*

"LUBRIPLATE Pure Tac Light contains no components derived from TSE/BSE relevant animal species; therefore, it is compliant with the requirements of the TSE Note for Guidance EMA/410/01 Rev. 3 July 2011".

