



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE FGL-CC

"This product is certified OU Kosher Pareve"

"This product is Halal certified"

*NSF International H-1 Registered
NSF ISO21469 Certification

DESCRIPTION

LUBRIPLATE FGL-CC has been developed specifically for use in centralized and automatic lubrication systems on high-speed can-closing equipment.

APPLICATIONS

LUBRIPLATE FGL-CC has years of successful field service in the beverage industry. LUBRIPLATE Division has worked closely with both original equipment manufacturers and beverage processors to ensure that LUBRIPLATE FGL-CC meets the severe demands of this application. LUBRIPLATE FGL-CC can also be used in other equipment where centralized lubrication systems are used such as fillers and packaging equipment.

ADVANTAGES

- ⇒ Unique thickening structure resists oil separation often encountered using conventional food grade greases.
- ⇒ High temperature stability and oxidation resistance.
- ⇒ Excellent resistance to water washout.
- ⇒ Provides outstanding rust and corrosion protection.
- ⇒ Effective anti-wear additives result in superior wear protection.
- ⇒ Excellent batch-to-batch consistency eliminates grease hardening which can be a common problem for many food grade greases while in storage.

Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Thickener		Aluminum Complex
Penetration Range 60 Strokes	ASTM D-217	370 - 410
NLGI No.		0/00
Dropping Point	ASTM D-566	450°F
Four Ball Wear Test	ASTM D-2266	0.38 mm
Water Washout (175°F)	ASTM D-1264	<8%
Oxidation Stability 100 hours	ASTM D-942	2.0 psi
Base Fluid Properties: Viscosity		Proprietary
Flash Point °F/°C	ASTM D-92	500°F
Pour Point °F/°C	ASTM D-97	0°F
Color	Visual	White
Texture	Visual	Smooth

PACKAGING AVAILABLE

Part No.

35 lb Pail	L0229-035
120 lb. Quarter Size, Drum	L0229-039
415 lb. Full Size, Drum	L0229-040

***NSF International H-1 Registration No.**
(Meets former USDA 1998 Guidelines)

043530

*Registered H-1 by NSF International for use in food processing facilities as a lubricant or anti-rust agent on equipment in which there may be incidental contact involving the lubricated part and the edible product.

"LUBRIPLATE FGL-CC contains no components derived from TSE/BSE relevant animal species; therefore, it is compliant with the requirements of the TSE Note for Guidance EMA/410/01 Rev. 3 July 2011".

