



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE SYN ST HIGH PERFORMANCE H-1 SPECIAL

"These products are certified OU Kosher Pareve"

*NSF International H-1 Registered
NSF ISO21469 Certification

DESCRIPTION

LUBRIPLATE Syn ST High Performance H-1 Special is a silicone-based grease, thickened with PTFE.

APPLICATIONS

It is a food-grade grease that is compatible with EPDM Rubber and other non-silicone elastomers. It is an excellent lubricant for O-rings and seals used in beverage and food processing and dispensing equipment.

"Please be advised that LUBRIPLATE Syn ST High Performance H-1 Special is not compatible with oxygen (O₂) and should not be recommended for any application where there is a possibility of this product coming in contact with any form of oxygen (both liquid and gas)"

ADVANTAGES

It is resistant to hot water, steam and alkaline solutions.

Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Type		Silicone
Temp. Service Range °C		-50 to 150
Viscosity @ 40°C	ASTM D-445	360.5 cSt
Viscosity Index	ASTM D-2270	>300
Flash Point °C	ASTM D-92	>310
Pour Point °C	ASTM D-97	-55
Thickener		PTFE
Color	Visual	White
Appearance	Visual	Smooth
NLGI Grade		3
Penetration: Unworked	ASTM D-217	230
Worked 60X	ASTM D-217	240
Dropping Point °C	ASTM D-2265	>260

**Please be advised that Worked Penetration may increase or vary depending on storage conditions and time. This physical change has no effect on product performance.



PACKAGING AVAILABLE

Package of 10/19 oz. Cartridges
50 lb. Pail

Part No.

L0365-010
L0365-035

***NSF International H-1 Registration No.**
(Meets former USDA 1998 Guidelines)

142599

Registered H-1 by NSF International for use in food processing facilities as a lubricant or anti-rust agent on equipment in which there may be incidental contact involving the lubricated part and the edible product.

"LUBRIPLATE Syn ST High Performance H-1 Special contains no components derived from TSE/BSE relevant animal species; therefore, it is compliant with the requirements of the TSE Note for Guidance EMA/410/01 Rev. 3 July 2011."