



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE SUPER FML LUBRICANTS

"These products are certified OU Kosher Pareve"

"These products are Halal certified"

*NSF International H-1 Registered
NSF ISO21469 Certification

DESCRIPTION

LUBRIPLATE Super FML Lubricants are among the most popular in the food industry as indicated by recent industry surveys. LUBRIPLATE FML Lubricants are white in color and due to their unexcelled lubrication characteristics, offer the utmost in lubrication and cleanliness. LUBRIPLATE FML greases provide exceptional anti-wear properties.

APPLICATIONS

- ⇒ Various food processing operations where a Class H-1 lubricant is required.

ADVANTAGES

- ⇒ USP White Mineral-Oil Based Food Grade Grease
- ⇒ These multi-purpose greases have been leaders in the food processing industry for years
- ⇒ Available in 3 NLGI grades for a wide variety of applications



Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS		
		FML-0	FML-1	FML-2
Soap		Anhydrous Calcium	Anhydrous Calcium	Anhydrous Calcium
NLGI No.		0	1	2
Penetration Worked:	ASTM D-217			
@ 77°F		355 to 385	310 to 340	265 to 295
Dropping Point	ASTM D-566	280°F/ 138°C	285°F/ 141°C	285°F/ 141°C
Mineral Oil Viscosity:	ASTM D-2161			
SUS @ 100°F		750	750	750
cSt @ 40°C	ASTM D-445	144	144	144

PACKAGING AVAILABLE

	FML-0	FML-1	FML-2
Case, 12/16 oz. Plastic Tubs	***	***	L0145-004
Case, 4/6 lb. Plastic Tubs	***	***	L0145-005
35 lb. Pail	L0143-035	L0144-035	L0145-035
115 lb. Quarter Size Drum	L0143-039	L0144-039	
120 lb. Quarter Size Drum	***	***	L0145-039
410 lb. Full Size Drum	L0143-040	L0144-040	L0145-040
Case, 12/11 oz. Aerosol Cans	***	***	L0145-063
Case, 40/14 oz. Cartridges	***	***	L0145-098
Bulk Bins	(Contact your LUBRIPLATE District Manager)		

*NSF International H-1 Registration No.'s
(Meets former USDA 1998 Guidelines)

125742

125740

125741

126087
(Aerosol)

Registered H-1 by NSF International for use in food processing facilities as a lubricant or anti-rust agent on equipment in which there may be incidental contact involving the lubricated part and the edible product.

"The LUBRIPLATE FML Series contains no components derived from TSE/BSE relevant animal species; therefore, it is compliant with the requirements of the TSE Note for Guidance EMA/410/01 Rev. 3 July 2011."