



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE SUPER HDS 10 MOTOR OIL

DESCRIPTION

LUBRIPLATE Super HDS 10 Motor Oil is premium quality engine oil for all-season used in commercial mixed-fleet engine operations. LUBRIPLATE Super HDS 10 Motor Oil is manufactured to meet the performance requirements in all naturally aspirated, turbocharged and supercharged diesel engines as well as all four-cycle gasoline engines.

Meets or exceeds the following specifications:

- ⇒ API CF
- ⇒ API CE (obsolete)
- ⇒ API CD
- ⇒ API SJ
- ⇒ API SH
- ⇒ Mil-L-2104F

APPLICATIONS

LUBRIPLATE Super HDS 10 Motor Oil is recommended for all major automotive diesel and mixed fleet (diesel/four cycle gasoline engines) operations in all service and under all operating conditions where the equipment owner specifies the use of single grade engine oils.

ADVANTAGES

- ⇒ Resisted breakdown under high temperatures
- ⇒ Maintained oil pressure under heavy load conditions
- ⇒ Minimized rust and corrosion
- ⇒ Good low temperature pour point



Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Viscosity cSt @ 40°C	ASTM D-445	45
Viscosity cSt @ 100°C	ASTM D-445	7.3
SAE Grade		10
Viscosity Index	ASTM D-2270	122
Sulfated Ash % wt	ASTM D-874	<1.0
Pour Point, °F	ASTM D-5950	-39
TBN (min)	ASTM D-2896	7.5

PACKAGING AVAILABLE

Carton, 12/1 Quart Plastic Bottles
5 Gallon Pail
55 Gallon Drum

Part No.

L0788-054
L0788-060
L0788-062