



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE SUPER 345 MOTOR OIL SAE 5W-30

DESCRIPTION

LUBRIPLATE Super 345 Motor Oil SAE 5W-30 is a superior-quality, high detergent automotive engine oil specially formulated with synthetic base stocks and mineral oil for better fuel economy and to reduce harmful emissions while meeting and exceeding the OEM's stringent lubrication requirements of today's engines.

LUBRIPLATE Super 345 Motor Oil SAE 5W-30 is formulated using an advanced additive package that provides maximum protection against wear, rust, corrosion, thermal breakdown, acid formation, reduces sludge build up and the formation of sludge and varnish deposits.

Meets or exceeds the following specifications:

- ⇒ API Service Category SN, SM, SL, SJ, SH, SG, SF, SE, SD, SC
- ⇒ Energy Conserving, ILSAC GF-5
- ⇒ Meets or exceeds the requirements of MIL-1-46152E
- ⇒ Ford WSS-M2C929-A (5W30)
- ⇒ DaimlerChrysler DC MS-639N, MS-6395L
- ⇒ GM 6094M specification (5W30), GM 9986231 (SAE 5W30)
- ⇒ Toyota service fill requirements for 5000-mile service intervals

APPLICATIONS

LUBRIPLATE Super 345 Motor Oil SAE 5W-30 can be used in passenger cars, light trucks and sport utility vehicles under all operating conditions.

ADVANTAGES

- ⇒ Friction-modified for improved fuel economy
- ⇒ Protects against sludge and varnish formation
- ⇒ Helps protect emissions system
- ⇒ Minimized rust and corrosion
- ⇒ Good low temperature pour point
- ⇒ Excellent resistance to viscosity and thermal breakdown at high temperatures



Typical Test Data

| PROPERTY | TEST METHOD | TYPICAL RESULTS |
|-----------------------|-------------|-----------------|
| Viscosity cSt @ 100°C | ASTM D-445 | 10.5 |
| 6600 cP max @ Deg C | | -35 |
| SAE Grade | | 5W30 |
| Viscosity Index | ASTM D-2270 | 155 |
| Specific Gravity | ASTM D-4052 | 0.872 |
| Flash Point, COC (°F) | ASTM D-92 | 400 |
| Pour Point, °C (min) | ASTM D-5950 | -35 |

PACKAGING AVAILABLE

Carton, 12/1 Quart Plastic Bottles
5 Gallon Pail
55 Gallon Drum

Part No.

L0732-054
L0732-060
L0732-062