



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE FMO-150-AW-OR

"This product is certified OU Kosher Pareve"

*NSF International H-1 Registered
NSF ISO21469 Certification

DESCRIPTION

LUBRIPLATE FMO-150-AW-OR was developed to meet the ever-increasing demands of pressure, speed and temperature that are placed on modern food processing machinery.

ADVANTAGES

LUBRIPLATE FMO-150-AW-OR is manufactured with clear, non-toxic, USP white mineral oil and is fortified with anti-oxidants, corrosion inhibitors, anti-wear agents and foam suppressants. LUBRIPLATE FMO-150-AW-OR is colored orange with a natural oil soluble dye. It is recommended for use in fluid power and lubrication systems with filtration systems of 10 microns or less. The orange color helps detect system leaks.

APPLICATIONS

LUBRIPLATE FMO-150-AW-OR is recommended for use in hydraulic systems, bearings, oil recirculating systems and gear cases where an oil of this viscosity is specified.

Typical Test Data

| PROPERTY | TEST METHOD | TYPICAL RESULTS |
|-------------------------------|-------------|-----------------|
| Viscosity: | | |
| SUS @ 100°F | ASTM D-2161 | 162 |
| SUS @ 210°F | ASTM D-2161 | 43 |
| cSt @ 40°C | ASTM D-445 | 32 |
| cSt @ 100°C | ASTM D-445 | 5 |
| Viscosity Index | ASTM D-2270 | 71 |
| Color | Visual | Orange |
| API Gravity | ASTM D-287 | 29.1 |
| Flash Point °F/°C | ASTM D-92 | 370/188 |
| Fire Point °F/°C | ASTM D-92 | 415/213 |
| Pour Point °F/°C | ASTM D-97 | -30/-34 |
| Neutralization No. | ASTM D-974 | 0.7 |
| 4-Ball Wear Scar Diameter, mm | ASTM D-4172 | .39 |
| Aniline Point, °F | ASTM D-611 | 215 |
| ISO Viscosity Grade | ASTM D-2422 | 32 |
| SAE No. | | 10 |

PACKAGING AVAILABLE

55 Gallon Drum

Part No.

L0889-062

*NSF International H-1 Registration No.
(Meets former USDA 1998 Guidelines)

142302

*Registered H-1 by NSF International for use in food processing facilities as a lubricant or anti-rust agent on equipment in which there may be incidental contact involving the lubricated part and the edible product.

"LUBRIPLATE FMO-150-AW-OR contains no components derived from TSE/BSE relevant animal species; therefore, it is compliant with the requirements of the TSE Note for Guidance EMA/410/01 Rev. 3 July 2011."

