



Sales, Service & Distribution Center
 Newark, NJ 07105
 Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center
 Toledo, OH 43605
 Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support
 Phone: 1-800-733-4755

FISKE AW Hydraulic Oils – ISO 32, 46, 68

*NSF H2 Registered

The FISKE AW Hydraulic Oils are high performance, anti-wear products for all types of hydraulic and recirculating systems found on industrial, construction and automotive equipment. They are fortified with rust and oxidation inhibitors and have outstanding demulsibility. The anti-wear additive package helps minimize the formation of sludge and other corrosive by-products which can cause reduction of pump life, filter blocking and interfere with efficient hydraulic power transfer. All three FISKE AW Hydraulic Oils have been designed to meet Cincinnati Milacron and Vickers hydraulic oil specifications. Their high aniline points help prolong seal life.

<u>Typical Tests</u>	<u>AW 32</u>	<u>AW 46</u>	<u>AW 68</u>
Viscosity cSt @ 40°C	29.43	41.91	60.8
Viscosity SUS @ 100°F	154	213	314
Viscosity SUS @ 210°F	43.5	47.5	53.8
Viscosity Index	97	99	103
Flash Point	405°F/207°C	410°F/210°C	430°F/221°C
Fire Point	445°F/230°C	450°F/232°C	470°F/243°F
Pour Point	-25°F/-32°C	-20°F/-29°C	-10°F/-23°C
Gravity	32.6	32.1	31.2
Color	L-1	L-1.5	L-2
Aniline Point	220°F	240°F	250°F
<u>Packaging Available</u>	<u>AW-32</u>	<u>AW-46</u>	<u>AW-68</u>
5-Gallon Pail	F0400-060	F0401-060	F0402-060
55-Gallon Drum	F0400-062	F0401-062	F0402-062
*NSF H2 Registration No's	<u>141055</u>	<u>141056</u>	<u>141057</u>

*These products are acceptable as lubricants where there is no possibility of food contact (H2) in and around food processing areas. Such compounds may be used as lubricants, release agents, or antirust films on equipment and machine parts in locations in which there is no possibility of the lubricant or lubricated part contacting edible products.