



FISKE BROTHERS REFINING COMPANY

NEWARK, NEW JERSEY 07105 • TOLEDO, OHIO 43605

FISKE'S GG OIL

GG Oil is an unusual mineral oil with a low viscosity possessing good fluidity and exceptional cooling properties. With its light viscosity, it has an unusually high flash point of 270°F./132°C. This oil is highly recommended for glass grinding operations and is used as is.

GG Oil meets the requirements for a high grade electrical discharge machining fluid (EDM Fluid). It may be recommended against Cincinnati Milacron Specification P-71, Light Dielectric Fluid.

GG Oil has good metalworking properties and affords excellent surface lubrication. It is recommended for soft metals, also for machining of magnesium and 70/30 brass, copper and aluminum.

GG Oil can also be used as a diluent where it is necessary to reduce the viscosity of various type of cutting fluids.

TYPICAL CHARACTERISTICS:

Viscosity @ 100°F., SUS/cSt	42/5
Flash Point °F/°C	270/132
API Gravity	37.2
Sulfur	No
Active Sulfur	No
Chlorine	No
Fatty Material	No
Color	L-0.5
Density	7.06 lbs/Gal
Pour Point	-12°C

GG Oil is available in the following:

Packaging Available

53 gallon drum

Part Number

F0538-062

Printed in U.S.A.
Revised 9/23/14