



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE SEAMER OIL FG SERIES

ISO-100 & ISO-150

"These products are certified OU Kosher Pareve"

*NSF International H-1 Registered
NSF ISO21469 Certification

DESCRIPTION

LUBRIPLATE SEAMER OILS FG ISO-100 & ISO-150 are manufactured with the highest quality NSF International H-1 food grade registered/USP mineral oils. USP mineral oil is the purest, safest and most effective oil available for use in H-1/food grade lubricating fluids. These fluids are compounded with anti-wear additives and rust and oxidation inhibitors which compliment the unsurpassed lubricating ability of the USP mineral oil.

APPLICATIONS & ADVANTAGES

LUBRIPLATE SEAMER FG OILS are specifically designed to lubricate can seaming machines, such as Angelus Seamer Models 61H, 120L, 121L, 140S & 180S.

These high-performance food grade seamer oils are recommended for can seamers with once-through oil systems as well as those that utilize oil re-circulating/filtration systems.

Manufactured with ingredients that comply with FDA 21 CFR 178.3570.

LUBRIPLATE's Free Oil Analysis service is provided to assist in monitoring oil condition in models equipped with oil re-circulating/filtration systems.

Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS	
		FG-100	FG-150
Viscosity:	cSt @ 40°C	109	151
	cSt @ 100°C	12	14
Viscosity Index	ASTM D-2270	102	99
Color		L0.5	L0.5
API Gravity	ASTM D-287	29.2	28.9
Flash Point	ASTM D-92	495°F/ 257°C	450°F/ 232°C
Fire Point	ASTM D-92	545°F/ 285°C	540°F/ 282°C
Pour Point	ASTM D-97	0°F/ -18°C	0°F/ -18°C
Neutralization No.		0.8	0.8
Aniline Point, °F		258	254
ISO Viscosity Grade		100	150
4-Ball Wear Test: 40 Kg., 1200 rpm, 167°F, 1 Hour, Average Wear Scar Diameter, mm	ASTM D-4172	.38	.38
Turbine Oil Oxidation Test: Hours to 2.0 Neut. No.	ASTM D-943	10,000+	10,000+

PACKAGING AVAILABLE

	FG-100	FG-150
55 Gallon Drum	L0908-062	L0909-062
330 Gallon Spacekraft Bin	L0908-070	L0909-070

*NSF International H-1 Registration No.'s
(Meets former USDA 1998 Guidelines)

143566

143600

*Registered H-1 by NSF International for use in food processing facilities as a lubricant or anti-rust agent on equipment in which there may be incidental contact involving the lubricated part and the edible product.

"LUBRIPLATE SEAMER FG OILS contain no components derived from TSE/BSE relevant animal species; therefore, it is compliant with the requirements of the TSE Note for Guidance EMA/410/01 Rev. 3 July 2011."

