



Fiske Brothers Refining Co.
dba LUBRIPLATE Lubricants Co.
1500 Oakdale Avenue
Toledo, OH, USA, 43605
Telephone: (419) 691-2491

LUBRIPLATE SYNXTREME HT MAX

L0331-002

SDS Preparation Date (mm/dd/yyyy): 06/08/2016

Page 1 of 10

SAFETY DATA SHEET

SECTION 1. IDENTIFICATION

Product identifier used on the label

: **LUBRIPLATE SYNXTREME HT MAX**

Product Code(s)

: L0331-002

Recommended use of the chemical and restrictions on use

: Lubricating grease.
No restrictions on use known.

Chemical family

: Mixture of: Halogenated aliphatic hydrocarbon polymers

Name, address, and telephone number of the supplier:

Fiske Brothers Refining Co. dba LUBRIPLATE Lubricants Co.

1500 Oakdale Avenue
P.O. Box 8038, Station A
Toledo, OH, USA
43605

Supplier's Telephone #

: (419) 691-2491 (Monday - Friday, 8:30 am - 4:30 pm, Eastern Time)

24 Hr. Emergency Tel #

: CHEM-TEL: (800) 255-3924 (Within Continental U.S.); CHEM-TEL: +1 (813) 248-0585 (Outside U.S., please call collect).

Name, address, and telephone number of the manufacturer:

Refer to supplier

SECTION 2. HAZARDS IDENTIFICATION

Classification of the chemical

White, grease like, semi-solid. No odor.

Most important hazards:

If product is heated, inhalation of fumes released from product may cause 'polymer fume fever', a flu-like illness. Occupational exposure to the substance or mixture may cause adverse effects. For further information, please refer to section 11 of the SDS.

This material is not classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Label elements

Signal Word

None required under OSHA HazCom2012 and 2015 Canadian WHMIS regulations.

Hazard statement(s)

None required under OSHA HazCom2012 and 2015 Canadian WHMIS regulations.

Precautionary statement(s)

None required under OSHA HazCom2012 and 2015 Canadian WHMIS regulations.

Other hazards

Other hazards which do not result in classification:

Toxic fumes may be released during a fire. Direct eye contact may cause slight or mild, transient irritation. May cause gastrointestinal irritation. If product is heated, inhalation of fumes released from product may cause 'polymer fume fever', a flu-like illness.

Environmental precautions:

Avoid release to the environment. See ECOLOGICAL INFORMATION, Section 12.



Fiske Brothers Refining Co.
dba LUBRIPLATE Lubricants Co.
1500 Oakdale Avenue
Toledo, OH, USA, 43605
Telephone: (419) 691-2491

LUBRIPLATE SYNXTREME HT MAX

L0331-002

SDS Preparation Date (mm/dd/yyyy): 06/08/2016

Page 2 of 10

SAFETY DATA SHEET

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

<u>Chemical name</u>	<u>Common name and synonyms</u>	<u>CAS #</u>	<u>Concentration (% by weight)</u>
Fluorinated grease	Synthetic lubricating grease	N/Ap (Mixture)	100%

The components are not hazardous or are below required disclosure limits.

SECTION 4. FIRST-AID MEASURES

Description of first aid measures

- Ingestion* : Do not induce vomiting. Never give anything by mouth to an unconscious person. If symptoms develop, seek medical attention.
- Inhalation* : If inhaled, move to fresh air. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen by qualified medical personnel only. If irritation or symptoms develop, seek medical attention.
- Skin contact* : For skin contact, wash with soap and water while removing contaminated clothing. If irritation or symptoms develop, seek medical attention.
- Eye contact* : Flush contaminated area with lukewarm, gently running water for at least 5 to 10 minutes or until the chemical is removed. If irritation or symptoms develop, seek medical attention.

Most important symptoms and effects, both acute and delayed

- : The thermal decomposition vapors of fluorinated polymers may cause polymer fume fever with flu-like symptoms in humans, especially when smoking contaminated tobacco. Symptoms of 'polymer fume fever' may include fever, chills, headache, nausea and muscle pain.
Direct eye contact may cause slight or mild, transient irritation. Symptoms may include stinging and tearing.
Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Indication of any immediate medical attention and special treatment needed

- : Provide general supportive measures and treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media

- : Use media suitable to the surrounding fire such as water fog or fine spray, alcohol foams, carbon dioxide and dry chemical.

Unsuitable extinguishing media

- : None known.

Special hazards arising from the substance or mixture / Conditions of flammability

- : Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure. Toxic fumes may be released during a fire.

Flammability classification (OSHA 29 CFR 1910.106)

- : Not classified as flammable.

Hazardous combustion products

- : Carbon oxides; Hydrogen fluoride; Carbon tetrafluoride; Carbonyl fluoride; Fluorocarbons; Other unidentified organic compounds.



LUBRIPLATE SYNXTREME HT MAX

L0331-002

SDS Preparation Date (mm/dd/yyyy): 06/08/2016

Page 3 of 10

SAFETY DATA SHEET

Special protective equipment and precautions for firefighters

Protective equipment for fire-fighters

- : Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Normal protective clothing (bunker gear) may not be adequate. A full-body encapsulating chemical protective suit may be necessary.

Special fire-fighting procedures

- : Move containers from fire area if safe to do so. Water spray may be useful in cooling equipment exposed to heat and flame. Do not allow run-off from fire fighting to enter drains or water courses. Dike for water control.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

- : All persons dealing with the clean-up should wear the appropriate personal protective equipment. Keep all other personnel upwind and away from the spill/release. Restrict access to area until completion of clean-up. Refer to protective measures listed in sections 7 and 8.

Environmental precautions : Ensure spilled product does not enter drains, sewers, waterways, or confined spaces.

Methods and material for containment and cleaning up

- : Ventilate the area. Prevent further leakage or spillage if safe to do so. Eliminate all ignition sources. Scrape up product and place it into a container for disposal. Use inert, non-combustible absorbents to assist the pick up of material. Keep in properly labelled containers. Material can create slippery conditions. Wash area thoroughly with a detergent solution and rinse well with water. Contact the proper local authorities. Refer to Section 13 for disposal of contaminated material.

Special spill response procedures

- : If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response center in the United States (phone: 1-800-424-8802).
US CERCLA Reportable quantity (RQ): None known.

In Canada: Contact appropriate local and provincial environmental authorities for assistance and/or reporting requirements.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling

- : Use with adequate ventilation. Wear protective equipment during handling. Avoid breathing fumes, mists or vapors. Avoid contact with skin, eyes and clothing. Keep away from extreme heat and direct flame. Keep away from incompatibles. Keep container tightly closed when not in use. Wash thoroughly after handling. Enforce no smoking in areas where fluoropolymers are handled or stored.

Conditions for safe storage : Store in a cool, dry, well-ventilated area. Store away from incompatibles and out of direct sunlight. Store locked up. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks.

Incompatible materials : Fluorine; Chlorine trifluoride; Strong fluorinating agents; Molten alkali metals.



LUBRIPLATE SYNXTREME HT MAX

L0331-002

SDS Preparation Date (mm/dd/yyyy): 06/08/2016

Page 4 of 10

SAFETY DATA SHEET

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:

<u>Chemical Name</u>	<u>ACGIH TLV</u>		<u>OSHA PEL</u>	
	<u>TWA</u>	<u>STEL</u>	<u>PEL</u>	<u>STEL</u>
Fluorinated grease	N/Av	N/Av	N/Av	N/Av

Exposure controls

Ventilation and engineering measures

- : Provide adequate ventilation. Local ventilation is recommended if the product is misted or used in a confined space, or if the TLV is exceeded.

Respiratory protection

- : If airborne concentrations are above the permissible exposure limit or are not known, use NIOSH-approved respirators. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with OSHA (29 CFR 1910.134) or CSA Z94.4-02.

Skin protection

- : Gloves impervious to the material are recommended. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Depending on conditions of use, an impervious apron should be worn. at high temperatures: Where extensive exposure to product is possible, use resistant coveralls, apron and boots to prevent contact.

Eye / face protection

- : Wear as appropriate: Safety glasses with side shields; Tightly fitting safety goggles.

Other protective equipment

- : An eyewash station and safety shower should be made available in the immediate working area. Other equipment may be required depending on workplace standards.

General hygiene considerations

- : Avoid breathing fumes, mists or vapors. Avoid contact with skin, eyes and clothing. Do not eat, drink or smoke when using this product. Upon completion of work, wash hands before eating, drinking, smoking or use of toilet facilities. Remove soiled clothing and wash it thoroughly before reuse. Handle in accordance with good industrial hygiene and safety practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : White, grease like, semi-solid.

Odor : None.

Odor threshold : N/Av

pH : N/Av

Melting/Freezing point : > 300°C (572°F)

Initial boiling point and boiling range

: > 300°C (572°F)

Flash point : None.

Flashpoint (Method) : N/Av

Evaporation rate (BuAe = 1) : Negligible

Flammability (solid, gas) : Not applicable.

Lower flammable limit (% by vol.)

: None.

Upper flammable limit (% by vol.)

: None.

Oxidizing properties : None known.

Explosive properties : Not explosive

Vapor pressure : Negligible.



LUBRIPLATE SYNXTREME HT MAX

L0331-002

SDS Preparation Date (mm/dd/yyyy): 06/08/2016

Page 5 of 10

SAFETY DATA SHEET

Vapor density : N/Av
Relative density / Specific gravity : 1.98 @ 25°C (77°F)
Solubility in water : Insoluble.
Other solubility(ies) : N/Av
Partition coefficient: n-octanol/water or Coefficient of water/oil distribution : N/Av
Auto-ignition temperature : N/Av
Decomposition temperature : N/Av
Viscosity : Semi-solid. Viscosity varies with shear rate.
Volatiles (% by weight) : N/Av
Volatile organic Compounds (VOC's) : N/Av
Absolute pressure of container : N/Av
Flame projection length : N/Av
Other physical/chemical comments : No additional information.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not normally reactive.
Chemical stability : Stable under normal conditions.
Possibility of hazardous reactions : Hazardous polymerization does not occur.
Conditions to avoid : Ensure adequate ventilation, especially in confined areas. Avoid contact with incompatible materials. Avoid heat and open flame.
Incompatible materials : Fluorine; Chlorine trifluoride; Strong fluorinating agents; Molten alkali metals.
Hazardous decomposition products : None known, refer to hazardous combustion products in Section 5.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Routes of entry inhalation : YES
Routes of entry skin & eye : YES
Routes of entry Ingestion : YES
Routes of exposure skin absorption : NO

Potential Health Effects:

Signs and symptoms of short-term (acute) exposure

Sign and symptoms Inhalation

: If product is heated, inhalation of fumes released from product may cause 'polymer fume fever', a flu-like illness. Symptoms of 'polymer fume fever' may include fever, chills, headache, nausea and muscle pain.

Sign and symptoms ingestion

: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Sign and symptoms skin

: Causes little or no irritation.



LUBRIPLATE SYNXTREME HT MAX

L0331-002

SDS Preparation Date (mm/dd/yyyy): 06/08/2016

Page 6 of 10

SAFETY DATA SHEET

- Sign and symptoms eyes* : Direct eye contact may cause slight or mild, transient irritation. Symptoms may include stinging and tearing.
- Potential Chronic Health Effects** : None known or reported by the manufacturer.
- Mutagenicity** : No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
- Carcinogenicity** : No components are listed as carcinogens by ACGIH, IARC, OSHA or NTP.
- Reproductive effects & Teratogenicity** : This product is not expected to cause reproductive or developmental effects.
- Sensitization to material** : Not expected to be a skin or respiratory sensitizer.
- Specific target organ effects** : Not classified as a specific target organ toxicity-single exposure.
 Not classified as a specific target organ toxicity - repeated exposure.
- Medical conditions aggravated by overexposure** : Pre-existing skin, eye and respiratory disorders.
- Synergistic materials** : None known or reported by the manufacturer.
- Toxicological data** : Not classified for acute toxicity based on available data.

<u>Chemical name</u>	<u>LC₅₀(4hr)</u>	<u>LD₅₀</u>	
	<u>inh, rat</u>	<u>(Oral, rat)</u>	<u>(Rabbit, dermal)</u>
Fluorinated grease	N/Av	> 5000 mg/kg (supplier)	N/Av

- Other important toxicological hazards** : None known or reported by the manufacturer.

SECTION 12. ECOLOGICAL INFORMATION

- Ecotoxicity** : The product is not classified as environmentally hazardous.
 No data is available on the product itself. The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters.
- Persistence and degradability** : Not expected to be rapidly biodegradable.
- Bioaccumulation potential** : No data is available on the product itself.
- Mobility in soil** : No data is available on the product itself.
- Other Adverse Environmental effects** : No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13. DISPOSAL CONSIDERATIONS

- Handling for Disposal** : Handle waste according to recommendations in Section 7. Since emptied containers may retain product residue, follow label warnings even after container is emptied.
- Methods of Disposal** : Dispose in accordance with all applicable federal, state, provincial and local regulations.
- RCRA** : If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.



Fiske Brothers Refining Co.
 dba LUBRIPLATE Lubricants Co.
 1500 Oakdale Avenue
 Toledo, OH, USA, 43605
 Telephone: (419) 691-2491

LUBRIPLATE SYNXTREME HT MAX

L0331-002

SDS Preparation Date (mm/dd/yyyy): 06/08/2016

Page 7 of 10

SAFETY DATA SHEET

SECTION 14. TRANSPORTATION INFORMATION

Regulatory Information	UN Number	UN proper shipping name	Transport hazard class(es)	Packing Group	Label
TDG	None.	Not regulated.	Not regulated	None	
TDG Additional information	None.				
49CFR/DOT	None.	Not regulated.	Not regulated	None	
49CFR/DOT Additional information	None.				
IMDG	None.	Not regulated.	Not regulated	None	
IMDG Additional information	None.				
ICAO/IATA	None.	Not regulated.	Not regulated	None	
ICAO/IATA Additional information	None.				

Special precautions for user : Appropriate advice on safety must accompany the package.

Environmental hazards : This product does not meet the criteria for an environmentally hazardous mixture, according to the IMDG Code. See Section 12 for more environmental information.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

: Not applicable.

SECTION 15 - REGULATORY INFORMATION

US Federal Information:

Components listed below are present on the following U.S. Federal chemical lists:

<u>Ingredients</u>	CAS #	TSCA Inventory	CERCLA Reportable Quantity(RQ) (40 CFR 117.302):	SARA TITLE III: Sec. 302, Extremely Hazardous Substance, 40 CFR 355:	SARA TITLE III: Sec. 313, 40 CFR 372, Specific Toxic Chemical	
					Toxic Chemical	de minimus Concentration
Fluorinated grease	N/Ap (Mixture)	Components: Present	None.	None.	None.	N/Ap

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes: None. Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds for the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.



Fiske Brothers Refining Co.
 dba LUBRIPLATE Lubricants Co.
 1500 Oakdale Avenue
 Toledo, OH, USA, 43605
 Telephone: (419) 691-2491

LUBRIPLATE SYNXTREME HT MAX

L0331-002

SDS Preparation Date (mm/dd/yyyy): 06/08/2016

Page 8 of 10

SAFETY DATA SHEET

US State Right to Know Laws:

The following chemicals are specifically listed by individual States:

<u>Ingredients</u>	CAS #	California Proposition 65		State "Right to Know" Lists					
		Listed	Type of Toxicity	CA	MA	MN	NJ	PA	RI
Fluorinated grease	N/Ap (Mixture)	No	N/Ap	No	No	No	No	No	No

Canadian Information:

CEPA information: All ingredients are listed on the DSL, or are exempted materials.

Canadian National Pollutant Release Inventory (NPRI): This product does not contain any substances listed on the NPRI.

WHMIS information: Refer to Section 2 for a WHMIS Classification for this product.

International Information:

Components listed below are present on the following International Inventory list:

<u>Ingredients</u>	CAS #	European EINECs	Australia AICS	Philippines PICCS	Japan ENCS	Korea KECI/KECL	China IECSC	New Zealand IOC
Fluorinated grease	N/Ap (Mixture)	Components: Polymer	Components: Present	Components: Present	Components: Present	Components Present	Components : Present	Components: May be used as a single component chemical under an appropriate group standard

SECTION 16. OTHER INFORMATION

Legend

- : ACGIH: American Conference of Governmental Industrial Hygienists
- AICS: Australian Inventory of Chemical Substances
- CA: California
- CAS: Chemical Abstract Services
- CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980
- CFR: Code of Federal Regulations
- DOT: Department of Transportation
- ENCS: Existing and New Chemical Substances
- EPA: Environmental Protection Agency
- HMIS: Hazardous Materials Identification System
- HSDB: Hazardous Substances Data Bank
- IARC: International Agency for Research on Cancer
- IATA: International Air Transport Association
- ICAO: International Civil Aviation Organisation
- IMDG: International Maritime Dangerous Goods
- Inh: Inhalation
- IOC: Inventory of Chemicals
- IUCLID: International Uniform Chemical Information Database
- KECI: Korean Existing Chemicals Inventory
- KECL: Korean Existing Chemicals List
- LC: Lethal Concentration



Fiske Brothers Refining Co.
 dba LUBRIPLATE Lubricants Co.
 1500 Oakdale Avenue
 Toledo, OH, USA, 43605
 Telephone: (419) 691-2491

LUBRIPLATE SYNXTREME HT MAX

L0331-002

SDS Preparation Date (mm/dd/yyyy): 06/08/2016

Page 9 of 10

SAFETY DATA SHEET

LD: Lethal Dose
 MA: Massachusetts
 MN: Minnesota
 mppcf: million particles per cubic foot
 MSHA: Mine Safety and Health Administration
 N/Ap: Not Applicable
 N/Av: Not Available
 NFPA: National Fire Protection Association
 NIOSH: National Institute of Occupational Safety and Health
 NJ: New Jersey
 NOEC: No observable effect concentration
 OECD: Organisation for Economic Co-operation and Development
 NTP: National Toxicology Program
 OSHA: Occupational Safety and Health Administration
 PA: Pennsylvania
 PEL: Permissible exposure limit
 PICCS: Philippine Inventory of Chemicals and Chemical Substances
 RCRA: Resource Conservation and Recovery Act
 RI: Rhode Island
 RTECS: Registry of Toxic Effects of Chemical Substances
 SARA: Superfund Amendments and Reauthorization Act
 SDS: Safety Data Sheet / Material Safety Data Sheet
 STEL: Short Term Exposure Limit
 TDG: Canadian Transportation of Dangerous Goods Act & Regulations
 TLV: Threshold Limit Values
 TWA: Time Weighted Average
 TSCA: Toxic Substance Control Act
 WHMIS: Workplace Hazardous Materials Identification System

References

- : 1. ACGIH, Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices for 2016.
- 2. International Agency for Research on Cancer Monographs, searched 2016.
- 3. Canadian Centre for Occupational Health and Safety, CCIInfoWeb databases, 2016 (Chempendium, HSDB and RTECs).
- 4. Material Safety Data Sheets from manufacturer.
- 5. US EPA Title III List of Lists - March 2015 version.
- 6. California Proposition 65 List - May 20, 2016 version.
- 7. OECD - The Global Portal to Information on Chemical Substances - eChemPortal, 2016.

Preparation Date (mm/dd/yyyy)

: 06/08/2016

Other special considerations for handling

: Provide adequate information, instruction and training for operators.

<p>Prepared for: Fiske Brothers Refining Co. dba LUBRIPLATE Lubricants Co. 1500 Oakdale Avenue Toledo, OH, USA 43605 Telephone: (419) 691-2491 Direct all enquiries to: Fiske Brothers Refining Co.</p>	
<p>Prepared by: ICC The Compliance Center Inc. Telephone: (888) 442-9628 (U.S.): (888) 977-4834 (Canada) http://www.thecompliancecenter.com</p>	



Fiske Brothers Refining Co.
dba LUBRIPLATE Lubricants Co.
1500 Oakdale Avenue
Toledo, OH, USA, 43605
Telephone: (419) 691-2491

LUBRIPLATE SYNXTREME HT MAX

L0331-002

SDS Preparation Date (mm/dd/yyyy): 06/08/2016

Page 10 of 10

SAFETY DATA SHEET

DISCLAIMER

This Safety Data Sheet was prepared by ICC The Compliance Center Inc. using information provided by Fiske Brothers Refining Co. and CCOHS' Web Information Service. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and Fiske Brothers Refining Co. expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other process.

This Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc. and Fiske Brothers Refining Co.

END OF DOCUMENT