



FISKE BROTHERS REFINING COMPANY

NEWARK, NEW JERSEY 07105 • TOLEDO, OHIO 43605

FISKE'S GG OIL

GG Oil is an unusual mineral oil with a low viscosity possessing good fluidity and exceptional cooling properties. With its light viscosity, it has an unusually high flash point of 270°F./132°C. This oil is highly recommended for glass grinding operations and is used as is.

GG Oil meets the requirements for a high-grade electrical discharge machining fluid (EDM Fluid). It may be recommended against Cincinnati Milacron Specification P-71, Light Dielectric Fluid.

GG Oil has good metalworking properties and affords excellent surface lubrication. It is recommended for soft metals, also for machining of magnesium and 70/30 brass, copper and aluminum.

GG Oil can also be used as a diluent where it is necessary to reduce the viscosity of various types of cutting fluids.

TYPICAL CHARACTERISTICS:

| | |
|-----------------------------|---------------|
| Viscosity @ 100°F., SUS/cSt | 42/5 |
| Flash Point °F./°C. | 270/132 |
| API Gravity | 37.2 |
| Sulfur | No |
| Active Sulfur | No |
| Chlorine | No |
| Fatty Material | No |
| Color | L-0.5 |
| Density | 7.06 lbs./Gal |
| Pour Point | -12°C |

GG Oil is available in the following:

Packaging Available

53 gallon drum
5 gallon pail

Part Number

F0538-062
F0538-035

Printed in U.S.A.
Revised 5/27/2025