



ISO-9001 Registered Quality System.  
ISO-21469 Compliant.

**Sales, Service & Distribution Center**  
Newark, NJ 07105  
Phone: 973-589-9150 Fax: 973-589-4432

**Manufacturing, Sales, Service & Distribution Center**  
Toledo, OH 43605  
Phone: 419-691-2491 Fax: 419-693-3806

**Sales and Tech Service Support**  
Phone: 1-800-733-4755

**PRODUCT DATA**

**LUBRIPLATE POWER HAMMER & CHISEL GREASE**

**DESCRIPTION**

This heavy-duty, extreme pressure, aluminum complex grease with molybdenum disulfide, copper and graphite is specifically designed for use on most types of heavy-duty power hammers.

**ADVANTAGES**

- ⇒ High performance for hydraulic power hammer/chisels & pile drivers
- ⇒ Super heavy duty, extreme pressure grease
- ⇒ Fortified with solids moly, copper and graphite
- ⇒ Provides excellent anti-wear protection
- ⇒ Greatly extends shaft and bushing life
- ⇒ Withstands high temperatures
- ⇒ Highly water resistant

**STORAGE RECOMMENDATIONS**

- ⇒ Products should be stored between 40°F-120°F
- ⇒ Products should be stored in a dry covered environment
- ⇒ Products should not be stored in warm, direct sunlight
- ⇒ Improper storage conditions can significantly alter the shelf life of the product. Such conditions would include temperature, moisture, open containers, etc.

**Typical Test Data**

PROPERTY	TEST METHOD	TYPICAL RESULTS*
NLGI Grade		2
Worked Penetration Range	ASTM D-217	265 - 295
Thickener Type		Aluminum Complex
Dropping Point (°F)	ASTM D-2265	514°F
4-Ball EP Test - OK Load	ASTM D-2596	520 kg.
4-Ball EP Test - Weld Load	ASTM D-2596	540 kg.
% Moly Present		1
% Copper Present		2
% Graphite Present		2
Viscosity @ 100°F (SUS)	ASTM D-88	1000 SUS
Viscosity @ 210°F (SUS)	ASTM D-88	73 SUS
Flash Point (COC) °F	ASTM D-92	420°F

**PACKAGING AVAILABLE**

**Part No.**

35 lb. Pail	L0190-035
120 lb. Quarter Size, Drum	L0190-039
Carton, 40/14.5 oz. Cartridges	L0190-098