



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center
Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center
Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support
Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE SUPER HDS 40 MOTOR OIL

DESCRIPTION

Meets or exceeds the following specifications:

- ⇒ API CF-2, CF
- ⇒ Detroit Diesel 2-stroke cycle engines, Oil Type 1 (1.0 % max. Sulfated ash)

APPLICATIONS

LUBRIPLATE Super HDS 40 Motor Oil is a high-quality diesel engine oil designed for use in a wide variety of applications, including off-highway diesel equipment, farm machinery, marine engines, 2-stroke cycle diesel engines (in the appropriate viscosity grades) and mixed commercial fleets. It may be also used in some heavy duty manual transmissions in trucks and busses.

ADVANTAGES

- ⇒ Excellent soot control for protection against abrasive wear and soot-induced oil thickening
- ⇒ Protects against sludge and varnish formation
- ⇒ Protects against scuffing and wear
- ⇒ Protects against rust and bearing corrosion
- ⇒ Good resistance to foaming and aeration
- ⇒ Low-ash content to minimize the formation of ash deposits and helps keep intake ports clean

Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Viscosity cSt @ 40°C	ASTM D-445	142
Viscosity cSt @ 100°C	ASTM D-445	15.0
SAE Grade		40
Viscosity Index	ASTM D-2270	106
Specific Gravity @ 60°F		0.886
Flash Point °C(°F)	ASTM D-92	235 (455)
Pour Point °C(°F)	ASTM D-5950	-27(-17)
TBN	ASTM D-2896	4.2
High-Temp/High-Shear Viscosity, cP @ 150°C		4.2
Zinc, wt%	ASTM D 5185	0.077
Sulfated Ash % wt	ASTM D-874	0.90

PACKAGING AVAILABLE

- Carton, 12/1 Quart Plastic Bottles
- 5 Gallon Pail
- 55 Gallon Drum

Part No.

- L0792-054
- L0792-060
- L0792-062