



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center
Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center
Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support
Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE METAL WORKING FLUID

DESCRIPTION

LUBRIPLATE Metal Working Fluid is a specially developed product suitable for a variety of metal working applications.

ADVANTAGES

- ⇒ Does not contain Fluorocarbons
- ⇒ Does not contain 1,1,1 Trichloroethane
- ⇒ Utilizes LUBRIPLATE'S SECURE STRAW DUAL SPRAY NOZZLE

APPLICATIONS

The 11-ounce aerosol can, including extension spout, makes it the ideal lubricant for:

- ⇒ Drilling
- ⇒ Sawing
- ⇒ Tapping
- ⇒ Grinding
- ⇒ Thread Chasing
- ⇒ Pipe Cutting
- ⇒ Filing
- ⇒ Nut Busting

TYPICAL TEST DATA

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Viscosity: SUS @ 100°F	ASTM D-2161	150
cSt @ 40°C	ASTM D-445	32
Viscosity: SUS @ 210°F	ASTM D-2161	45
cSt @ 100°C	ASTM D-445	6
ISO Grade		32
SAE Grade		10
Flash Point	ASTM D-92	310°F/154°C
Fire Point	ASTM D-92	350°F/177°C
Pour Point	ASTM D-97	-40°F/-40°C
Specific Gravity	ASTM D-4052	0.906
Color	ASTM D-1500	L-3

PACKAGING AVAILABLE

Part No.

Carton 12/11 oz. Aerosol Cans

L0185-063