



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE SUPER HDS 50 MOTOR OIL

DESCRIPTION

Meets or exceeds the following specifications:

⇒ API CF, SL

APPLICATIONS

LUBRIPLATE Super HDS 50 Motor Oil is a high-quality diesel engine oil designed for use in a wide variety of applications, including off-highway diesel equipment, farm machinery, marine engines, 2-stroke cycle diesel engines (in the appropriate viscosity grades) and mixed commercial fleets. It may be also used in some heavy-duty manual transmissions in trucks and buses.

ADVANTAGES

- ⇒ Excellent soot control for protection against abrasive wear and soot-induced oil thickening
- ⇒ Protects against sludge and varnish formation
- ⇒ Protects against scuffing and wear
- ⇒ Protects against rust and bearing corrosion
- ⇒ Good resistance to foaming and aeration

Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Viscosity cSt @ 40°C	ASTM D-445	224
Viscosity cSt @ 100°C	ASTM D-445	20.0
SAE Grade		50
Viscosity Index	ASTM D-2270	103
Specific Gravity @ 60°F		0.891
Flash Point, °C (°F)	ASTM D-92	240 (464)
Pour Point, °C (°F)	ASTM D-5950	-27 (-17)
High-Temp/High-Shear Viscosity, cP @ 150°C		5.7
TBN	ASTM D-2896	10.5
Zinc, wt%	ASTM D 5185	0.119
Sulfated Ash % wt	ASTM D-874	1.39

PACKAGING AVAILABLE

Carton, 12/1 Quart Plastic Bottles
5 Gallon Pail
55 Gallon Drum

Part No.

L0793-054
L0793-060
L0793-062