



Sales, Service & Distribution Center

Newark, NJ 07105

Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605

Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

FISKE'S Art & Mil Grease

Typical Tests

| | |
|---|--------------------------------|
| Type of Thickener | Anhydrous Calcium |
| Percent of Thickener | 8 - 13% |
| Worked Penetration 60 Strokes @ 77°F (ASTM D-217) | 265 - 295 |
| NLGI No. | 2 |
| Mineral Oil Properties: | |
| Viscosity @ 40°C | 13.0 - 17.0 mm ² /s |
| Viscosity @ 100°C (ASTM D-445) | 1.8 - 4.2 mm ² /s |
| Pour Point (ASTM D-97) | -50°F/-46°C |
| Flash Point (ASTM D-92) | 325°F/163°C |
| Dropping Point (ASTM D-566) | 280°F/138°C |
| Cold Test of Lubricant | -60°F/-51°C |
| Oxidation Stability Drop 100 Hours (ASTM D-942) | 5 psi/34.5 kPa |
| Color | Amber (translucent) |
| Character | Smooth |
| Rust Preventative Properties 48 hrs. @ 52°C. (ASTM D-1743) | Pass, no corrosion |

Meets and is an approved source for the following Ford Specifications:

ESB-M1C163-C

WSB-M1C163-D

Packaging Available

35 lb. Pail
390 lb. Drum

Part No's

F0115-035
F0115-040