



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE POWER HAMMER & CHISEL GREASE

DESCRIPTION

This heavy-duty, extreme pressure type, aluminum complex grease with moly, copper and graphite, is made for use on most types of heavy-duty power hammers.

ADVANTAGES

⇒ Greatly extends shaft and bushing life.

Typical Test Data

| PROPERTY | TEST METHOD | TYPICAL RESULTS* |
|----------------------------|-------------|------------------|
| NLGI Grade | | 2 |
| Worked Penetration Range | ASTM D-217 | 265 - 295 |
| Thickener Type | | Aluminum Complex |
| Dropping Point (°F) | ASTM D-2265 | 514°F |
| 4-Ball EP Test - OK Load | ASTM D-2596 | 520 kg. |
| 4-Ball EP Test - Weld Load | ASTM D-2596 | 540 kg. |
| % Moly Present | | 1 |
| % Copper Present | | 2 |
| % Graphite Present | | 2 |
| Viscosity @ 100°F (SUS) | ASTM D-88 | 1000 SUS |
| Viscosity @ 210°F (SUS) | ASTM D-88 | 73 SUS |
| Flash Point (COC) °F | ASTM D-92 | 420°F |

PACKAGING AVAILABLE

Part No.

35 lb. Pail

L0190-035

120 lb. Quarter Size, Drum

L0190-039

Carton, 40/14 oz. Cartridges

L0190-098