



ISO-9001 Registered Quality System.  
ISO-21469 Compliant.

**Sales, Service & Distribution Center**  
Newark, NJ 07105  
Phone: 973-589-9150 Fax: 973-589-4432

**Manufacturing, Sales, Service & Distribution Center**  
Toledo, OH 43605  
Phone: 419-691-2491 Fax: 419-693-3806

**Sales and Tech Service Support**  
Phone: 1-800-733-4755

## PRODUCT DATA

# LUBRIPLATE LPG WS ISO 150

## DESCRIPTION

LUBRIPLATE LPG 150 is a synthetic lubricant formulated for use in process gas compression applications that require wide operating temperature ranges and minimum interaction between the lubricant and the process gas.

## APPLICATIONS

LUBRIPLATE LPG 150 is intended for the lubrication of reciprocating compressors processing natural gas, carbon dioxide or other hydrocarbon gases. LUBRIPLATE LPG 150 may also be used as a cylinder lubricant for natural gas, carbon dioxide and other gases that require chemical resistance in an ISO-150 viscosity grade.

## Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS
<b>Viscosity:</b>		
cSt @ 40°C	ASTM D-445	146 cSt
cSt @ 100°C	ASTM D-445	28 cSt
Viscosity Index	ASTM D-2270	235 cSt
Pour Point	ASTM D-97	< -40°C
Flash Point, COC	ASTM D-92	520°F
Four ball wear	ASTM D-4172	0.37 mm
Foam, Sequence I (air and Natural gas)	ASTM D-892	0 mL
Specific Gravity, 60°F	ASTM D-4052	1.05
Copper Strip Corrosion	ASTM D-130	1B
Appearance	Visual	Clear, pinkish

## PACKAGING AVAILABLE

55 Gallon Drum  
275 Gallon Bin

## Part No.

L1011-062  
L1011-072