



ISO-9001 Registered Quality System.  
ISO-21469 Compliant.

**Sales, Service & Distribution Center**  
Newark, NJ 07105  
Phone: 973-589-9150 Fax: 973-589-4432

**Manufacturing, Sales, Service & Distribution Center**  
Toledo, OH 43605  
Phone: 419-691-2491 Fax: 419-693-3806

**Sales and Tech Service Support**  
Phone: 1-800-733-4755

## PRODUCT DATA

# LUBRIPLATE MP-4 Multipurpose Lubricant Penetrating Oil

### DESCRIPTION

#### ONE PRODUCT TO SATISFY FOUR IMPORTANT CONSIDERATIONS:

- ⇒ Protects against Wear
- ⇒ Releases Stuck Parts
- ⇒ Prevents Rust
- ⇒ Displaces Moisture

### APPLICATIONS & ADVANTAGES

#### Moisture Displacement

- ⇒ An excellent "wet start" product, featuring outstanding moisture displacement properties

#### Rust Preventive Coating

- ⇒ Possesses exceptional rust-proofing properties. Thirty-day test in humidity cabinet prove its rust-proofing properties. Light in viscosity, promotes rapid and complete draining.
- ⇒ Highly recommended for rust-proofing machine tool parts, steel cast parts, etc.

#### Penetrating Fluid

- ⇒ Exceptional penetration properties.
- ⇒ Recommended for nuts, bolts, valves, heat risers, cables, linkage, etc.

#### Lubricant

- ⇒ In addition to all the other properties, recommended for permanent and positive lubrication over a long period of time.
- ⇒ Aerosol package utilizes LUBRIPLATE'S SECURE STRAW DUAL SPRAY NOZZLE

### Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Viscosity: SUS @ 100°F	ASTM D-2161	45
cSt @ 40°C	ASTM D-445	6
SUS @ 210°F	ASTM D-2161	31
cSt @ 100°C	ASTM D-445	1.5
Flash Point	ASTM D-92	280°F/138°C
Fire Point	ASTM D-92	305°F/152°C
Dielectric Strength	ASTM D-877 A	42 kV (average)
Color	ASTM D-1500	5
Appearance	Visual	Clear to Hazy

#### PACKAGING AVAILABLE

Carton 12/12 oz. Aerosol Cans  
Case 12/14 oz. Pump Spray

#### Part No.

L0722-063  
L0722-067