



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center
Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center
Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support
Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE SYNXTREME HT MAX FLUSH

DESCRIPTION

LUBRIPLATE SYNXTREME HT MAX FLUSH is a non-flammable fluorosolvent that may be used as a diluent for fluorinated lubricants or a cleaning agent for these products.

SAFETY

LUBRIPLATE SYNXTREME HT MAX FLUSH does not contain hazardous ingredients. However, carrier solvent must be properly ventilated. See the Safety Data Sheet for additional safety related information on the lubricant.

STORAGE RECOMMENDATIONS

1. Products should be stored between 40°F-120°F.
2. Products should be stored in a dry covered environment.
3. Products should not be stored in warm, direct sunlight.
4. improper storage conditions can significantly alter the shelf life of the product. Such conditions would include temperature, moisture, open containers, etc.

SPECIFICATIONS

The typical properties reported on this technical data sheet should not be used for preparing specifications on this lubricant. Please contact LUBRIPLATE for assistance in preparing a specification.

Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Color	Visual	Colorless
Flash Point	ASTM D92	None
Boiling Point	CTM	80°C min.
Density, 25C	CTM	1750 g/l
Surface Tension	Report	14 dynes/cm

PACKAGING AVAILABLE

Carton – 1 Quart Jug

Part No.

L1019-050

LUBRIPLATE SYNXTREME HT MAX FLUSH contains no components derived from TSE/BSE relevant animal species; therefore, it is compliant with the requirements of the TSE Note for Guidance EMA/410/01 Rev. 3 July 2011.